



Product Comparison



Dell Wyse D50D

Operating System	Linux, Dell Wyse-enhanced SUSE Linux
Processor	AMD G-Series T48E Dual Core 1.4GHz
Memory	Standard: 2GB Flash / 2GB RAM DDR3-1066MHz; Maximum: 8GB Flash / 4GB RAM; SSD storage also supported
I/O peripheral support	<ul style="list-style-type: none">• One DisplayPort. (Optional DisplayPort to DVI-I adapter available)• One DVI-I port. DVI to VGA (DB-15) adapter included• Four external USB 2.0 ports (2 front, 2 back)• Serial and parallel connectivity supported through USB 2.0 adapters
Networking	<ul style="list-style-type: none">• 10/100/1000 Base-T Gigabit Ethernet• Optional single and dual band 802.11 a/b/g/n integrated wireless with external dual antenna• Optional RJ45 connector or SFP Module support for Fiber NIC network connectivity
Display	<ul style="list-style-type: none">• VESA monitor support with Display Data Control (DDC) for automatic setting of resolution and refresh rate• DisplayPort: 2560x1600@32bpp• DVI-I: 1920x1200@32bpp• Dual display: 1920x1200@32bpp
Audio	<ul style="list-style-type: none">• Composite audio jack: 1/8-inch mini, 16-bit stereo• Internal mono speaker
Graphics	AMD Radeon™ HD 6250
Included	<ul style="list-style-type: none">• Enhanced USB keyboard with Windows keys (104 keys) and PS/2 mouse port• PS/2 optical mouse
Power	<ul style="list-style-type: none">• Worldwide auto-sensing 100-240 VAC, 50/60 Hz 65W, 19V DC• Energy Star V.5.2 Phase V external and EuP compliant power adapter



Dell Wyse Z50D

Operating System	Linux, Dell Wyse-enhanced SUSE Linux
Processor	Dual-core AMD G-T56N 1.65 GHz
Memory	2GB Flash / 2GB RAM DDR3. Configurable to 64GB Flash / 4GB RAM
I/O peripheral support	<ul style="list-style-type: none">• One DisplayPort (optional DisplayPort to DVI-D adapter available, sold separately)• One DVI-I port, DVI to VGA (DB-15) adapter included• Six total USB ports: Four USB 2.0 ports (two front, two rear) and two SuperSpeed USB 3.0* ports on rear (backwards-compatible with USB 2.0)• Factory options: Legacy connectivity (adds two serial ports, 1 parallel port and 1 PS/2 port)
Networking	<ul style="list-style-type: none">• 10/100/1000 Gigabit Ethernet• Optional internal wireless 802.11 a/b/g and dual-band n
Display	<ul style="list-style-type: none">• VESA monitor support with Display Data Control (DDC) for automatic setting of resolution and refresh rate• DisplayPort: 2560x1600@32bpp• DVI-I: 1920x1200@32bpp• Dual display: 1920x1200@32bpp
Audio	<ul style="list-style-type: none">• Output: 1/8-inch mini jack, full 16-bit stereo, 48KHz sample rate; Digital audio out, internal mono speaker• Input: 1/8-inch mini jack, 8-bit microphone
Graphics	AMD Radeon HD 6320 graphics (integrated with APU)
Included	<ul style="list-style-type: none">• Keyboard: Enhanced USB keyboard with Windows Keys (104 keys) and PS/2 mouse port• Pointing device: PS/2 Optical mouse included
Power	Worldwide auto-sensing 100-240 VAC, 50/60 Hz. Energy Star V.5.2 Phase V compliant power supply



Dell Wyse D50D

Power consumption	Under 9 watts (average)
Dimensions	<ul style="list-style-type: none">• Height: 6.7 inches (170mm)• Width: 1.6 inches (40mm)• Depth: 7.3 inches (185mm)
Mountings	<ul style="list-style-type: none">• Vertical feet standard.• Optional VESA mounting bracket for mounting to flat surfaces, such as walls.• Please note: D class clients cannot mount directly to the backs of monitors.• Optional Ergotron mounting stand for mounting with Dell monitors.
Temperature Range	<ul style="list-style-type: none">• Operating, vertical position: 32° to 104° F (10° to 40° C)• Storage: 14° to 140° F (-10° to 60° C)
Humidity	<ul style="list-style-type: none">• 20% to 80% condensing• 10% to 95% non-condensing
Security	Built-in Kensington security slot (cable sold separately)
Warranty	<ul style="list-style-type: none">• Three-year limited hardware warranty• Optional WyseChoice extensions and upgrades at http://www.wyse.com/warranties



Dell Wyse Z50D

Power consumption	Under 15 watts (average)
Dimensions	<ul style="list-style-type: none">• Height: 7.87 inches (200mm)• Width: 1.85 inches (47mm)• Depth: 8.85 inches (225mm)• Weight: 2.42 lbs (1.1kg)
Mountings	<ul style="list-style-type: none">• Vertical feet standard.• Horizontal feet optional*• Optional VESA mounting bracket for mounting to flat surfaces, such as walls.• Please note: Z class clients cannot mount directly to the backs of monitors.• Optional Ergotron mounting stand for mounting with Dell monitors.
Temperature Range	<ul style="list-style-type: none">• Horizontal position: 50° to 104° F (10° to 40° C)• Vertical position, power button up: 50° to 104° F (10° to 40° C)• Storage: 14° to 140° F (-10° to 60° C)
Humidity	<ul style="list-style-type: none">• 20% to 80% condensing• 10% to 95% non-condensing
Security	Built-in Kensington security slot (cable sold separately)
Warranty	<ul style="list-style-type: none">• Three-year limited hardware warranty• Optional WyseChoice extensions and upgrades at www.wyse.com/warranties.